

SPEAKMAN®

ANYSTREAM®



SD-02-AF



S-2252-AF

Showerheads

SD-02-AF

Polished chrome plated Anystream showerhead. Brass ball swivel joint. Brass shank. Contoured polished chrome plated brass spray adjusting handle. 2-3/4" face. 6 Lexan® self-cleaning, deposit resisting plungers with 48 spray channels. Water conserving pressure compensating Autoflo® device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1M Standard. 1/2" NPTF inlet.

S-2252-AF

Polished chrome plated Anystream showerhead. Brass ball swivel joint. Brass shank. Spray adjusting T-handle. 2-3/4" face. 6 Lexan self-cleaning, deposit resisting plungers with 48 spray channels. Water conserving pressure compensating Autoflo device reduces flow to 2.5 gpm/9.46 lpm maximum, to meet existing ANSI A112.18.1M Standard. 1/2" NPTF inlet.

OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> BP	Blister Pack Packaging
<input type="checkbox"/> BPT	1/2" British Pipe Thread Inlet
<input type="checkbox"/> PBL	Polished Brass PVD Coating (SD-02 only)
<input type="checkbox"/> SC	Satin Chrome (SD-02 only)
<input type="checkbox"/> SN	Satin Nickel Finish (SD-02 only)
<input type="checkbox"/> VR	Vandal-Resistant (S-2252-AF only)
<input type="checkbox"/> PC-PVD-BP	Chrome with Polished Brass Trim (S-2252-AF only)
<input type="checkbox"/> PCWHT	White with Polished Chrome Trim (S-2252-AF only)

SH2 This space for Architect/Engineer approval.

Speakman Company

P.O. Box 191, Wilmington, DE 19899-0191 USA
1-800-537-2107 Fax: 1-800-977-2747
www.speakmancompany.com

